



1.2m/4ft Standard Performance Dual Polarized Microwave Parabolic Antenna

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Famous
- Certification: CE ISO9001
- Model Number: XPD Antenna
- Minimum Order Quantity: 1 SET
- Price: Negotiable
- Packaging Details: Standard export packaging/customizable packaging
- Payment Terms: T/T L/C



Product Specification

- Name: Microwave Antenna
- Diameter Of Mounting Pole: $\Phi 114$ Mm
- Fine Azimuth Adjustment: Coarse 360° Fine $\pm 15^\circ$
- Fine Elevation Adjustment: Fine $\pm 10^\circ$
- Wind Velocity Operational: 180km/h
- Wind Velocity Survival: 200km/h
- Ice-load: 25.4 Mm
- Operational Temperature: $-55 \sim +70$
- Highlight: **34 dbi parabolic antenna 1.2m,
32 dbi parabolic antenna 4ft,
XPD 1.2m Microwave Parabolic Antenna**

for more products please visit us on mw-antenna.com

Product Description

1.2m/4ft Standard Performance Dual-Polarized Microwave Parabolic Antenna

Our patent split-lobe microwave communication parabolic antenna for large diameter, which can save packaging and transportation costs greatly without any quality compromised

High performance ultra high XPD parabolic antennas – Excellent performance for a wide range of applications

Simple Assembly – Minimal required assembly simplifies installation on site and guarantees "factory-tested" quality

Electrical performance:

Antenna Model	Antenna Size(m/ft)	Frequency (GHZ)	Gain(dBi)			3dB BW (degs)	XPD (dB)	VSW R	F/B radio dB)	ISO
			Low	Mid	Top					
CMP124DA	1.2m/4ft	4.4-5.0	32.0	32.6	33.1	3.7	30	1.2	58	35
CMP126WDA	1.2m/4ft	5.925-7.125	34.9	35.7	36.5	2.7	30	1.15	61	35
CMP127WDA	1.2m/4ft	7.125-8.5	36.5	37.3	38.0	2.2	30	1.15	63	35
CMP1210WDA	1.2m/4ft	10-11.7	39.6	40.2	40.8	1.6	30	1.15	65	35
CMP1213WDA	1.2m/4ft	12.2-13.25	41.6	41.7	41.9	1.3	30	1.15	66	35
CMP1215DA	1.2m/4ft	14.4-15.35	42.6	42.9	43.2	1.1	30	1.15	66	35

Mechanical performance:

Diameter of Mounting Pole	Φ114 mm
Fine Azimuth Adjustment	Coarse 360° Fine ±15°
Fine Elevation Adjustment	Fine ±10°
Wind Velocity Operational	180km/h
Wind Velocity Survival	200km/h
Ice-load	25.4 mm
Operational Temperature	-55~ +70

1.The low/mid/high gain has≤-0.5dBi tolerance is within the normal range;

2.F/Bradio:Denotes highest radiation relative to the main beam,at 180°±40°,across the band.Production antennas do not exceed rated values by more than 2 dB unless stated otherwise;



Wuxi Famous Communication Equipment Co., Ltd.

+86 13255118228

eric@mw-antenna.com

mw-antenna.com

Room 803, Wisdom Building, No. 18 Wisdom Road, Huishan Economic Development Zone, Huishan District, Wuxi City, Jiangsu Province, China